




DECKTOP ARCHITECTURAL TILES

PRODUCT DESCRIPTION

Rubber Tiles

for Decking Applications

Designed specifically for decking applications, DeckTOP Architectural Tiles from EMC provide the perfect combination of beauty, functionality and ease of installation. DeckTop tiles can be installed over any firm flat surface, including fragile waterproof membranes, **without using adhesives**.



When installed using our SureKONNECT pins, DeckTOP tiles create a durable “floating” deck system that protects the roof from the elements, while providing excellent drainage.

While the DeckTOP tiles may appear to be identical to their softer playground tile cousins, this product is made from higher density materials for enhanced durability and puncture resistance.

DeckTOP tiles are porous and permeable. Rain and snow melt will quickly flow through the tiles to the waterproof surface below. Robust drainage grooves have been molded into the base of these tiles to allow water to easily flow laterally under the tiles. These grooves form a network of channels that are perfectly sized to allow wiring to be installed under the tiles.



DeckTOP Architectural Tiles are available in a variety of pigmented and premium EPDM colors. Transition ramps are also available. Weighing in at less than six pounds per square foot, this material offers superior protection while also providing excellent thermal and acoustic insulation.



BENEFITS:

- *Easy to Install* - SureKONNECT pins keep the tiles in place without attaching to your roof deck
- *Smooth Surface* - comfortable underfoot while providing exceptional slip resistance, wet or dry
- *Easy to Maintain* - requires only basic cleaning with a broom, vacuum or hose

Distributed by



800-842-2914

dsafety@sbcglobal.net
www.diamond-safety.com

DECKTOP ARCHITECTURAL TILES

TECHNICAL DATA



Go GREEN



Be SAFE



Standard Colors



Black

Blue



Red

Gray



Earth

Green



Green Black

Gray Black



Blue Black

Tan Black



Red Black

Description

DeckTOP Architectural Tiles are a 1 3/8" thick resilient and slip resistant safety tile that helps to protect your roof or deck in public traffic areas. These tiles are porous and permeable offering excellent drainage.

DeckTOP Architectural Tiles are made from 100% post-consumer waste tires. They provide an exceptionally durable, safe, low maintenance alternative to the heavy, pedestal type concrete pavers.

Uses

DeckTOP Architectural Tiles are ideally suited to improve the beauty, comfort and ease of maintenance in various environments including Rooftop Decks, Plazas, Patios, Walkways and more.

Advantages

- **DeckTOP Architectural Tiles** are highly durable and easy to install without using adhesives.
- **DeckTOP Architectural Tiles** are ADA compliant and meet ASTM and SPSC requirements.
- **DeckTOP Architectural Tiles** have a unique grooved bottom design that provides superior drainage. These grooves also allow for easy placement of small cables or wires.
- **DeckTOP Architectural Tiles** are environmentally friendly, molded from 100% California recycled waste tires. Each tile diverts up to 2.5 tires from our landfills.
- **DeckTOP Architectural Tiles** are safe, containing no toxic materials and certified to be 100% steel free.
- **DeckTOP Architectural Tiles** have a soft, smooth surface texture, providing comfort underfoot while maintaining exceptional slip resistance in wet or dry conditions.
- **DeckTOP Architectural Tiles** are modular in design making them easy to handle and easy to install.

Advantages (Continued)

- **DeckTOP Architectural Tiles** come in a variety of colors providing a multitude of design options to meet any need.
- **DeckTOP Architectural Tiles** are available with either a Flat Top or a Brick Top Pattern.
- **DeckTOP Architectural Tiles** are easy to maintain requiring only basic cleaning with a broom, vacuum or water hose on a regular basis.
- **DeckTOP Architectural Tiles** are produced by the industries' leading manufacturer of rubber molded safety tiles and accessories. This product is backed by a **Five Year Limited Material Warranty**.



Product Specification

| | |
|-----------------|------------------|
| Tile Size: | 24" x 24" ± 1/8" |
| Tile Thickness: | 1 3/8" |
| Tile Weight: | 21lbs |

Physical Properties

| Characteristic | Test | Result |
|-------------------|------------|------------------|
| Flame Spread: | ASTM E108 | Class A |
| Flammability: | ASTM E648 | Class II |
| Flammability: | ASTM 2859 | Pass |
| Toxicity: | ASTM 2075 | Lead Free |
| Slip Resistance: | ASTM D2047 | .84 |
| Skid Resistance: | ASTM E303 | Dry 96, Wet 47 |
| Tensile Strength: | ASTM D412 | 1175.3 psi |
| Wear Resis- | ASTM D3884 | 1.64% Loss/3000c |
| | QPanel QUV | <3.0/4032 ksqm |

Packaging

| | |
|--------------------|-------------|
| Pieces Per Pallet: | 144 |
| Weight Per Pallet: | 3069 |
| Pallet Dimensions: | 48"x48"x60" |