



**LEGEND:**

- ① Kid Kusion Tile (See Specifications for Depth and Color)
- ② SureLOCK Clip
- ③ Minimum 1.0% Slope - 1/4" / 12"
- ④ Sidewalk or Curb per Specification
- ⑤ Concrete or Asphalt underlying Lip per Specification
- ⑥ Geotextile Fabric Overlapped 12" and Tape Joints
- ⑦ Minimum 1/2" Fine Crushed Granite Screenings to Achieve a Max 1/4" Variation in Grade
- ⑧ Compacted Granular A Type 1 To 95% S.P.D. (See Specification for Depth)
- ⑨ 3/4" Clear Stone, 6" Radius
- ⑩ 4" Perforated Plastic or PVC Drain Pipe at 16' On Center
- ⑪ Compacted Subgrade

Thickness	CRITICAL FALL HEIGHT	REVISIONS			
		REV	DESCRIPTION	DATE	APPROVAL
		0	Original Issue	06/03/2010	Ron Loyd
1.50"	4.0'				
2.50"	6.0'				
3.50"	8.0'				
3.75"	10.0'				
File Name EMC100.60	Prepared By: J. Steel				

SHEET	SCALE	DWG No.	FSCM No.
-------	-------	---------	----------