


## Disc-O-Tred No. 787 DESIGN RUBBER STAIR TREADS



A new design nose - easily adjusts to steps with angle nosings between 90° and 60°; allows fit on stairways designed for safety or aesthetics. Ideal for public buildings where fire safety is a prime prerequisite; durable for heavy traffic areas. Circular discs (3/4" diameter) are easy to clean, affords safer pedestrian traffic. Meets Federal Specs. RR-T-650E. Install with No. 400 Neoprene Contact Adhesive or No. 300 Water-based Contact Adhesive, back of tread and back of nosing; use No. 110 Epoxy Nose Caulk inside of nose.

### SPECIFICATIONS:

Furnish and install No. 787 Disc-O-Tred Stair Treads by Musson Rubber Co., Akron, Ohio; 1/4" thick tapering to back edge; 12-1/2" deep. Treads shall have a Flame Spread Rating of 25 or less using ASTM-E-84 Test; an adjustable square nose (1-7/8" deep); a sanded back to assure proper adhesion; contain no asbestos fiber; made of top quality homogenous rubber compound, color extending throughout thickness; free from objectionable odors or imperfections which might impair serviceability. Select standard length of 36", 42", 48", 54", 60" or 72". Select standard solid color from Color Series III.

## Grit Strip Disc-O-Tred No. GS787



### SPECIFICATIONS:

Furnish and install No. GS787 Grit-Strip Disc-O-Tred Stair Treads by Musson Rubber Co., Akron, Ohio; 1/4" thick tapering to back edge, 12-1/2" deep, with two black\* 3/4" wide abrasive grit-strips inlaid in tread 1" from front edge, spaced 3/4" apart. Treads shall have a Flame Spread Rating of 25 or less using ASTM-E-84 Test; an adjustable square nose (1-7/8" deep), a sanded back to assure proper adhesion; contain no asbestos fiber; made of top quality homogenous rubber compound, color extending throughout thickness; free from objectionable odors or imperfections which might impair serviceability. Select standard length of 36", 42", 48", 54", 60" or 72". Select standard solid color from Color Series III.

## Grit Strip Disc-O-Tred No. GS787VI



### SPECIFICATIONS:

Furnish and install No. GS787VI Grit-Strip Disc-O-Tred Stair Treads by Musson Rubber Co., Akron, Ohio; 1/4" thick tapering to back edge, 12-1/2" deep, with one black\* 2" wide abrasive grit-strip inlaid in tread, 1" from front edge, for access by Visually Impaired. Treads shall have a Flame Spread Rating of 25 or less using ASTM-E-84 Test; an adjustable square nose (1-7/8" deep), a sanded back to assure proper adhesion; contain no asbestos fiber; made of top quality homogenous rubber compound, color extending throughout thickness; free from objectionable odors or imperfections which might impair serviceability. Select standard length of 36", 42", 48", 54", 60" or 72". Select standard solid color from Color Series III.

\*Grit Strip inserts are also available in Brown, Gray, Beige, Safety Yellow or Safety Red at an extra cost.

All items listed on this page fully meet the ASTM-E84 Flame Spread Rating of 25 or less.

#### Color Series III



All colors must be selected from actual samples