

Musson Rubber Step Cover Adhesives

No. 400 Neoprene Contact Adhesive

For bonding to all Disc-O-Treds, Rubber Stair Treads or Koroseal Vinyl Stair Treads to concrete, pan filled, wood, metal, marble and terrazzo steps. A rapid drying, long range contact cement; specially formulated for Musson stair coverings. Brush on application; use on back of treads and back of nosing. Contains solvents, extremely flammable. 1 gallon covers 75 lineal feet of stair treads (brush on back of tread and step). Ready to use in 1 quart, 1 gallon and 4 gallon containers.

[MSDS](#)

No. 300 Water-Based Contact Adhesive

A non-solvent based alternative to install rubber and vinyl stair treads and cove risers to concrete, wood, terrazzo, metal or marble. One gallon covers 75 lineal feet of stair treads (brush on back of tread and step). Ready to use in 1 quart, 1 gallon and 4 gallon containers.

[MSDS](#)

No. 560 Rubber Flooring Adhesive

Environmentally Friendly

For installing Rubber Floor Tiles or Rolls over suitable on-grade dry concrete floors, suspended concrete floors, or suspended wood floors. May also be used with sanded back molded rubber stair treads. Not recommended where excessive moisture exists; Non-Carcinogenic; Non-Toxic; safe for the environment and freeze thaw stable. See label for complete instructions. Ready to trowel in 1 gallon or 4 gallon cans. Covers 150 square feet per gallon.

[MSDS](#)

No. 775 Epoxy Adhesive

Environmentally Friendly

The only recommended adhesive for use with Disc-O-Tile. May be used with other rubber stair treads, tile and flooring. Because of flame spread properties, other adhesives will not bond Disc-O-Tile to the floor. A two-part solvent-free adhesive; contains 1 can Part A 1 can Part B, and a stirring paddle. Covers approximately 150 square feet per unit.

[MSDS](#)

No. 110 Epoxy Stair Nose Caulk

Environmentally Friendly

Epoxy Stair Nose Caulk is recommended for all Stair Tread installations; Nose Caulk is necessary when installing Adjusta-Nose treads or when the step nosing is broken, worn or rounded. This two-part Epoxy Caulk will fill voids at the nose of the step and give needed support underneath the stair tread nose. Nose Caulk can also be used to repair the top surface of the step. Two-part mixture in quart units (mixing instructions on label) or in 13.5 oz. Dual-Cartridge, for use with our professional Dual-Cartridge Dispenser. Dual-Cartridge saves time, labor, mess and cleanup as caulk mixes in nozzle as it is dispensed. Dual-Cartridge yields approx. 50 lin. ft. of 1/4" bead; quart unit yields approximately 75 ft.

[MSDS QUART \(part "A"\)](#)

[MSDS QUART \(part "B"\)](#)

[MSDS DUAL CARTRIDGE \(part "A"\)](#)

[MSDS DUAL CARTRIDGE \(part "B"\)](#)